

cnMatrix™ TX2000 Series Switches

QUICK LOOK:

- **Cloud Managed**
- **Non-Blocking, Fully Managed, Enterprise Grade, L2/L3 switch**
- **Cambium (GPS) Sync – Redundant dual sources**
- **Comprehensive/Intelligent PoE Solution**
- **Dual redundant AC/DC removable Power supplies**



cnMaestro™
XMS

Cambium Networks' next generation switching platform offers a cloud managed, high performance, feature rich enterprise grade ethernet switching solution.

The cnMatrix platform of switches provides:

- Full Line Rate, non-blocking architecture
- Easy and simple, free cloud (or on premise) management with cnMaestro™ or XMS*
- Zero-touch deployment of switches makes installation easy
- Policy Based Automation eliminates manual and time consuming configuration
- Enhanced Security with automated device profiling and segmentation
- Policy Based Automation eliminates manual configuration during adds, moves and changes of network devices
- Unified Wired-Wireless access solution

* Feature to be included in a future release.

The cnMatrix TX Series Switches provides the following functionality:

Cambium Sync

- Redundant Input Sync sources
 - » Internal GPS module (with external antenna)
 - » cnPulse
- Full per-port control with stats available

Comprehensive/Intelligent PoE solution

- 802.3af/at/bt - up to 90W
- 24V Passive PoE - up to 15W
- 54V Passive PoE - up to 90W

Dual redundant removable power supplies AC supplies

- 600W, 930W, & 1200W options

DC supplies

- Fully Isolated – Supports positive/negative input voltages
- 36V–72V
- 600W, 930W, & 1200W options
- Grounding lug nut located on front panel

All interfaces located on front panel

The cnMatrix series of fully managed switches delivers full Layer 2 and Layer 3 capabilities with enhanced access security. The cnMatrix series offers flexibility with SFP+ (10 Gbps) or SFP (1 Gbps) uplink ports. These switches come with a 3/5-Year Limited Lifetime Warranty.

cnMatrix™ TX2000 Series Switches

Specifications

	TX2012R-P	TX2020R-P
Throughput	104 Gbps	112 Gbps
Forwarding Rate in Mpps (64 Byte Packets)	120	120
10/100/1000 Mbps RJ45 Ports	8	16
1 Gbps Fiber Ports (SFP)	0	0
10 Gbps Fiber Ports (SFP+)	4	4
PoE+ Enabled Ports 802.3af/at/bt	8	16
Low Voltage Passive PoE (24 V)	4	8
High Power 4 PPOE (up to 90 W)	4	8
Serial Console	Yes	Yes
USB	Yes	Yes
Rack Mount Kit	No (optional accessory)	Yes
Internal Fans	2	2
Reset Button	Yes	Yes
MAC Address Table Size	16K	16K
Flash Storage	128 MB	128 MB
DRAM	512 MB	512 MB
VLANs	4K	4K
Port Based VLANs	4K	4K
LACP/Trunking	8 LAGs/8 links per LAG	8 LAGs/8 links per LAG
QoS Priority Queues	8	8
PVRST	32	32
Ingress/Egress ACL	128	128
Static ARP Entries	512	512
ARP Entries	512	512
Static Routes	64	64
Dynamic Routing	512	512
IGMP Multicast Groups	256	256
Policy Based Automation	Yes	Yes
Cambium Sync (via RJ45 ports)	8	16
Redunant Sync Sources	Yes	Yes
External Antenna Port	Yes	Yes
cnPulse Port	Yes	Yes
Removable Power Supply (CRPS)	1	2
Redundant Power Supplies	No	Yes

cnMatrix™ TX2000 Series Switches

Hardware Specifications

	TX2012R-P	TX2020R-P
Power Supply	CRPS dependent	CRPS dependent
Max Switch Power (WITH TRAFFIC)	38.88W	39.24W
MTBF (hours)	393648	250744
Unit Weight	2.24 kg (4.98 lbs)	4.3 kg (9.46 lbs)
Unit Dimensions (H x L x W)	4.4 x 25 x 26 cm (1.73 x 9.84 x 10.24 in)	4.4 x 35 x 44 cm (17.3 x 1.75 x 17.32 in)
Boxed Weight	2.73 kg (6 lbs)	5.35 kg (11.77 lbs)
Boxed Dimensions (H x L x W)	9.2 x 37.5 x 31.5 cm (3.62 x 14.76 x 12.4 in)	12.8 x 55.1 x 48.5 cm (5.04 x 21.69 x 19.09 in)
CPU Speed	800 MHz	800 MHz
LEDs per port	Link/Activity, PoE	Link/Activity, PoE
PoE Power Budget	CRPS dependent (see table)	CRPS dependent (see table)
802.3af/at/bt PoE (54V)	Ports 1–8	Ports 1–16
24V Passive PoE - up to 15W	Ports 5–8	Ports 9–16
54V Passive PoE - up to 90W	Ports 1–4	Ports 1–8
54V Passive PoE - up to 30W	Ports 5–8	Ports 9–16
PoE Max Power Per Port	30W/90W	30W/90W
Rack Mountable	Not included	Yes 1U
Wall Mountable	Yes (Optional Accessory)	Yes
Temperature Ranges	-10°C up to 65°C	-10°C up to 65°C
Operating Humidity	55°C at 95% RH	55°C at 95% RH
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)

cnMatrix™ TX2000 Series Switches

Specifications - All Models

Quality of Service	ACL mapping and marking of ToS/DSCP (COS)	Layer 2 Feature Set	802.1s multiple spanning tree
	ACL mapping marking of 802.1p		VLAN, Port, Protocol, 802.1q
	ACL mapping to priority queue		802.1d
	DiffServ support		802.1x authentication
	Honoring DSCP and 802.1p (CoS)		Auto MDI/MDIX
	Traffic shaping/metering		BPDU Guard, Root Guard
	Priority queue management using Weighted Round Robin (WRR), Strict Priority (SP) and a combination of WRR and SP		IGMP Snooping v1/v2/v3*, Fast Leave
Traffic Management	ACL-based inbound rate limiting policies		LLDP/LLDP MED
	Broadcast, multicast and unknown unicast rate limiting		IGMP Proxy
	Inbound rate limiting per port		Static MAC
	Outbound rate limiting per port/queue		Flow Control per port
Security	802.1x authentication		Per VLAN STP (PVST/PVRST)
	MAC authentication*		Port Mirroring: port based, ACL based, VLAN based
	DHCP snooping		Port Isolation/Private VLAN Edge
	RADIUS authentication/authorization	Link Aggregation Groups (Static/LACP)	
	Radius/Tacacs/Tacacs+	Rate Limiting/Storm Control	
	Authentication, Authorization, and Accounting (AAA)	Jumbo frame (9k)	
	Secure shell	DHCP Snooping	
	Secure copy (SCP)*	BPDU filtering	
	Local username/password	Broadcast/Multicast/Unlearned Unicast (Storm Control)	
		DoS Protection	
	Ping/TraceRoute/ICMPv6		

Layer 3 Feature Set

Inter-VLAN Routing

Static ARPs

Static Routes

DHCP Relay

Dynamic Routing – RIPv1/v2

Dynamic Routing – OSPFv2

Route Redistribution

* Feature to be included in a future release.

cnMatrix™ TX2000 Series Switches

Specifications - All Models cont'd

Management

cnMaestro (cloud management)	Simple Network Time Protocol (SNTP)
Industry standard Command Line Interface (CLI)	Local/remote system logging
DHCP Client	Policy Based Automation
Embedded web management (HTTP/HTTPS)	Display log messages multiple terminals*
Embedded DHCP server	TFTP/SFTP
USB file management and storage	Telnet client/server
Out-of-Band Ethernet Management	IPv6 management
SSH / SSH v2	Password management
SNMP v1/v2/v3	Autoinstall support for firmware images and config files
DHCP relay	

Security

PERMIT/DENY
ACTIONS FOR
INBOUND IP AND
LAYER 2 TRAFFIC
CLASSIFICATION
BASED ON:

Source/Destination IP address	EtherType
TCP/UDP Source/Destination port	IEEE 802.1p user priority
IP Protocol Type	VLAN ID
Type of Service (ToS) or differentiated services (DSCP) field	RFC 1858—Security Considerations for IP Fragment Filtering
Source/Destination MAC address	

* Feature to be included in a future release.

cnMatrix™ TX2000 Series Switches

Acoustic Noise dBA Per Switch (AMBIENT TEMPERATURE)

TX2012R-P

AC CRPS

1 x 1200W AC: 52.7 dB < 33°C, 52.8 dB 33°C-43°C, 53.5dB - >43°C,

1 x 930W AC: 51.3 dB < 33°C, 51.6 dB 33°C-43°C, 52dB - >43°C,

1 x 600W AC: 60 dB < 33°C, 59.8dB 33°C-43°C, 59.6dB - >43°C,

DC CRPS

1 x 1200W DC: 69.2 dB < 33°C, 70.5dB 33°C-43°C, 70.6dB - >43°C,

1 x 930W DC: 64.3 dB < 33°C, 68.5 dB 33°C-43°C, 68.5dB - >43°C,

1 x 600W DC: 59 dB < 33°C, 65.5 dB 33°C-43°C, 65.5dB - >43°C,

TX2020R-P

AC CRPS

1 x 1200W AC : 71.4 dB < 33°C, 71.5dB 33°C-43°C, 71.5dB - >43°C,

2 x 1200W AC : 55.6 dB < 33°C, 55.7dB 33°C-43°C, 56.1dB - >43°C,

1 x 930W AC : 67.9 dB < 33°C, 68.0dB 33°C-43°C, 68.1dB - >43°C,

2 x 930W AC : 54.8 dB < 33°C, 55.1dB 33°C-43°C, 55.4dB - >43°C,

1 x 600W AC : 58.2 dB < 33°C, 58.4dB 33°C-43°C, 58.6dB - >43°C,

2 x 600W AC : 52.8 dB < 33°C, 53.3dB 33°C-43°C, 53.9dB - >43°C,

DC CRPS

1 x 1200W DC : 68.9 dB < 33°C, 71.2dB 33°C-43°C, 71.2dB - >43°C,

2 x 1200W DC : 72.9 dB < 33°C, 74.0dB 33°C-43°C, 74.0dB - >43°C,

1 x 930W DC : 64.3 dB < 33°C, 68.9dB 33°C-43°C, 68.9dB - >43°C,

2 x 930W DC : 61.3 dB < 33°C, 68.6dB 33°C-43°C, 68.7dB - >43°C,

1 x 600W DC : 60.7 dB < 33°C, 66.6dB 33°C-43°C, 66.7dB - >43°C,

2x600W DC : 55.8 dB < 33°C, 67.3dB 33°C-43°C, 67.3dB - >43°C,

Power Supply	Type (AC/DC)	Available PoE Load	PoE Load	Temperature
1200W	AC	~1000W	<700W	-10°C up to 65°C
1200W	AC	~1000W	>700W	-10°C up to 65°C
1200W	DC	~960W	<700W	-10°C up to 65°C
1200W	DC	~960W	>700W	-10°C up to 65°C
930W	AC	~800W	<600W	-10°C up to 65°C
930W	AC	~800W	>600W	-10°C up to 65°C
930W	DC	~840W	<600W	-10°C up to 65°C
930W	DC	~840W	>600W	-10°C up to 65°C
600W	AC	~500W	<450W	-10°C up to 65°C
600W	AC	~500W	>450W	-10°C up to 65°C
600W	DC	~500W	<450W	-10°C up to 65°C
600W	DC	~500W	>450W	-10°C up to 65°C

cnMatrix™ TX2000 Series Switches

Part #	Power Supply	Type (AC/DC)	DC - in Voltage	Available PoE Load
MXCRPSAC1200A0	1200W (110V)	AC	NA	900W
MXCRPSAC1200A0	1200W (220V)	AC	NA	960W
MXCRPSDC1200A0	1200W	DC	48-72V	960W
MXCRPSDC1200A0	1200W	DC	36-47V	740W
MXCRPSAC930A0	930W	AC	NA	840W
MXCRPSDC930A0	930W	DC	48-72V	840W
MXCRPSDC930A0	930W	DC	36-47V	740W
MXCRPSAC600A0	600W	AC	NA	500W
MXCRPSDC600A0	600W	DC	48-72V	500W
MXCRPSDC600A0	600W	DC	36-47V	500W

IEEE Standards

Switching

Core Switching Features

- IEEE 802.1ab—Link Layer Discovery Protocol (LLDP)
- IEEE 802.1D—Spanning tree compatibility
- IEEE 802.1p—Ethernet priority with user provisioning and mapping
- IEEE 802.1s—Multiple spanning tree compatibility
- IEEE 802.1Q—Virtual LANs with port-based VLANs
- IEEE 802.1X—Port-based authentication

VLAN Support

- IEEE 802.1W—Rapid spanning tree compatibility
- IEEE 802.3—10BASE-T
- IEEE 802.3u—100BASE-T
- IEEE 802.3ab—1000BASE-T
- IEEE 802.3ac—VLAN tagging
- IEEE 802.3ad—Link aggregation
- IEEE 802.3x —Flow control
- Bridged Local Area Networks - Amendment 07: Multiple Registration Protocol

IEEE 802.1Q-2003

- RFC 4541—Considerations for Internet Group Management Protocol (IGMP) Snooping Switches
- ANSI/TIA-1057—LLDP-MEDia Endpoint Discovery (MED)

Advanced Layer 2 Features

- Authentication, Authorization, and Accounting (AAA)
- Broadcast/Multicast/Unknown unicast storm recovery
- DHCP Snooping
- IGMP Snooping Querier
- Independent VLAN Learning (IVL) support
- Jumbo Ethernet frame support
- Port MAC locking
- Port mirroring
- Protected ports
- Static MAC filtering

Layer 3 Features

- Inter-VLAN Routing
- Static ARP
- Static Routes
- RFC 2131 – DHCP Relay
- RFC 2328 – OSPF Version 2
- RFC 2453 – RIP Version 2

cnMatrix™ TX2000 Series Switches

System Facilities

Event and error logging facility

Run-time and configuration download capability

PING utility

FTP Transfers via IPv4/IPv6

RFC 768—UDP

RFC 783—TFTP

RFC 791—IP

RFC 792—ICMP

RFC 793—TCP

RFC 826—ARP

RFC 894—Transmission of IP datagrams over Ethernet networks

RFC 896—Congestion control in IP/TCP networks

RFC 951—BOOTP

RFC 1034—Domain names - concepts and facilities

RFC 1035—Domain names - implementation and specification

RFC 1321—Message digest algorithm

RFC 1534—Interoperability between BOOTP and DHCP

RFC 2021—Remote network monitoring management information base version 2

RFC 2030—Simple Network Time Protocol (SNTP)

RFC 2132—DHCP options and BOOTP vendor extensions

RFC 2819—Remote Network Monitoring Management Information Base

RFC 2865—RADIUS client

RFC 2869—RADIUS Extensions

RFC 3579—RADIUS support for EAP

RFC 3580—IEEE 802.1X RADIUS usage guidelines

RFC 3164—BSD syslog protocol

RFC 3580—802.1X RADIUS Usage Guidelines

* Feature to be included in a future release.

Management

SNMP v1, v2, and v3

SSH 1.5 and 2.0

RFC 4252—SSH authentication protocol

RFC 4253—SSH transport layer protocol

RFC 4254—SSH connection protocol

RFC 4251—SSH protocol architecture

RFC 4716—SECSH public key file format

RFC 4419—Diffie-Hellman group exchange for SSH transport layer protocol

SSL 3.0 and TLS 1.2

RFC 2246—TLS protocol, version 1.2

RFC 2818—HTTP over TLS

RFC 3268—AES cipher suites for transport layer security

Telnet

Web GUI

cnMatrix™ TX2000 Series Switches

SNMP MIBs

Enterprise MIBs for Full Configuration Support of Switching Features

RFC 1213—MIB II	RFC 2819—RMON groups 1, 2, 3, and 9
RFC 1493—Bridge MIB	RFC 2863—IF-MIB
RFC 1612—DNS resolver MIB extensions	RFC 2925—Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations
RFC 1643—Definitions of managed objects for Ethernet-like interface types	RFC 3273—RMON Groups 1, 2, and 3
RFC 2233—Interfaces group MIB using SMI v2	RFC 3291—Textual conventions for Internet network addresses
RFC 2613—SMON MIB	RFC 3434—RMON Groups 1, 2, and 3
RFC 2618—RADIUS authentication client MIB	RFC 4022—TCP-MIB
RFC 2674—VLAN MIB	RFC 4113—UDP-MIB
RFC 2737—Entity MIB version 2*	

* Feature to be included in a future release.

Quality of Service MIBs

MIBs for full configuration support of DiffServ, ACL, and CoS functionality	RFC 3289—Management information base for DiffServ architecture (read-only)
---	--

Quality of Service

Classify Traffic Based on Same Criteria as ACLs and Optionally:

Mark the IP DSCP or Precedence header fields	RFC 2475—An architecture for differentiated services
Police the flow to a specific rate with two-color aware support	RFC 2597—Assured forwarding Per-Hop Behavior
RFC 2474—Definition of the differentiated services field (DS field) in the IPv4 and IPv6 headers	

cnMatrix™ TX2000 Series Switches

Ordering Information			
Type	Model	Part Number	Description
Switch	TX2012R-P	MXTX2012GxPA10	Intelligent Ethernet PoE Switch, Cambium Sync, 8 x 1 Gbps, and 4 SFP+, Removable Power Supply (not included) - no pwr cord
Switch	TX2020R-P	MXTX2020GxPA10	Intelligent Ethernet PoE Switch, Cambium Sync, 16 x 1 Gbps and 4 SFP+, Removable & Redundant Power Supplies (not included) - no pwr cord
CRPS - AC		MXCRPSAC600A0	AC 600W total power, no power cord
CRPS - AC		MXCRPSAC930A0	AC 930W total power, no power cord
CRPS - AC		MXCRPSAC1200A0	AC 1200W total power, no power cord
CRPS - DC		MXCRPSDC600A0	DC 600W total power, 37V - 60V, includes 1.5 m cable connector
CRPS - DC		MXCRPSDC930A0	DC 930W total power, 37V - 60V, includes 1.5 m cable connector
CRPS - DC		MXCRPSDC1200A0	DC 1200W total power, 37V - 60V, includes 1.5 m cable connector
Power Cord		N000900L092A	AC line cord, US Type B, 15A, 1.2 m C13 connector
Power Cord		N000900L040A	AC line cord, US Type B, 1.2m C13 connector
Rack Ears		MX-EXTXFULLA-1	cnMatrix rack mount kit: Full-width switch

cnMatrix™ TX2000 Series Switches

Ordering Information

Type	Model	Part Number	Description
Transceiver	n/a	SFP-10G-SR	10G SFP+ MMF SR Transceiver, 850 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	n/a	SFP-1G-SX	1G SFP MMF SX Transceiver, 850 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	n/a	SFP-10G-LR	10G SFP+ SMF LR Transceiver, 1310 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	n/a	SFP-1G-LX	1G SFP SMF LX Transceiver, 1310 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	n/a	SFP-1G-Copper	1000 Base-T (RJ45) SFP Transceiver. -40°C to 85°C (-40°F to 185°F)
Transceiver	n/a	SFP-10G-Copper	10G Base-T (RJ45) SFP Transceiver. 0°C to 70°C (-40°F to 185°F)



TX2012R-P



TX2020R-P

ABOUT CAMBIUM NETWORKS

Cambium Networks delivers wireless communications that work for businesses, communities and cities worldwide. Millions of our radios are deployed to connect people, places and things with a unified wireless fabric that spans multiple standards and frequencies of fixed wireless and Wi-Fi, all managed centrally via the cloud. Our multi-gigabit wireless fabric offers a compelling value proposition over traditional fiber and alternative wireless solutions. We work with our Cambium certified ConnectedPartners to deliver purpose-built networks for service provider, enterprise, industrial, and government connectivity solutions in urban, suburban, and rural environments, with wireless that just works.